UNCLASSIFIED

AD 273 733

Reproduced by the

ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

273733

CATAINTO TY AST



86000

TEXACO EXPERIMENT INCORPORATED

RICHMOND 2, VIRGINIA

62-2-6

COMBUSTION OF ELEMENTAL BORON

Quarterly Summary Report for November 1961 through January 1962

TM-1326

U. V. Henderson, Jr., and Harry P. Woods

TEXACO EXPERIMENT INCORPORATED
Richmond 2, Virginia

Submitted to the Department of the Navy, Office of Naval Research, as partial fulfillment of requirements under contract NOnr-1883(00). Reproduction in whole or in part is permitted for any purposes of the United States Government.

CONTENTS

	Page
SUMMARY	3
INTRODUCTION	3
OXIDATION OF BORON WITH FLUORINE IN THE MASS SPECTROMETER	4
MICROBALANCE EXPERIMENTS	9
FUTURE WORK	13
REFERENCES	13

SUMMARY

Our earlier observation that boron monofluoride, BF, is the species evolved from the surface of a heated boron rod exposed to fluorine gas inside a mass spectrometer has been confirmed. Evidence also is presented that the rate of formation of BF is only slightly dependent on temperature above 1200°K.

Preliminary experiments in a microbalance apparatus show no detectable reaction between a high-purity polycrystalline boron rod at ambient temperature and fluorine gas at 1 to 200 μ Hg pressure. However, a boron rod heated to about 600°K in an image furnace gives a reaction rate of about 10^{16} molecules/cm²-sec at a fluorine pressure of 1 μ Hg. This value is subject to an upward revision since it corresponds to approximately total consumption of the fluorine at the flow rates possible with the equipment.

INTRODUCTION

Research on this contract has been concerned with investigating the combustion of elemental boron with various oxidizers to obtain a better understanding of this phenomenon. Results of research done on the combustion of boron with oxygen are given in references 1 through 3. Recently work has begun on the study of the combustion of boron with halogen oxidizers (4, 5). This report covers work done during the period November 1961 through January 1962.

OXIDATION OF BORON WITH FLUORINE IN THE MASS SPECTROMETER

Experiments run in a Bendix Time-of-flight Mass Spectrometer (Figures 1 and 2) indicate that there is apparently no reaction between BF₃ and a heated high-purity polycrystalline boron rod. The inlet system for the mass spectrometer in which these experiments were performed is described in reference 4b. As can be seen from the results given in Tables I and II, the relative intensity of the fragments formed by electron impact on the BF₃ remain constant to 1500°K. These data were obtained at a pressure of 10⁻⁶ torr (1 torr = 1 mm of Hg), corresponding to a flow rate of about 10¹⁵ molecules/sec.

The reaction of polycrystalline boron with fluorine in this apparatus confirms our earlier observation with ClF₃ as an oxidizer that the BF⁺ intensity is greater than can be accounted for by electron bombardment of BF₃ (4b). Typical results for the reaction of fluorine and boron are given in Tables III and IV. A comparison of the relative intensities of BF⁺ and BF₂⁺ in Table IV with the normal cracking pattern of BF₃ (Table II) indicates that BF is the species evolved from the boron surface; this seems to eliminate BF₂ as a first-reaction product. The apparent low ratio of BF₂⁺ to BF₃⁺ results from a high background at mass number 68 (BF₃⁺). This, of course, reduces the ratio of BF⁺ to BF₃⁺ also.

In order to relate the data obtained from the mass spectrometer to the surface reaction on the boron rod, the BF⁺ intensity due to ionization of BF was obtained as the difference between the total BF⁺ intensity and the BF⁺ intensity resulting from the fragmentation of BF₃ in the mass spectrometer. The latter intensity was determined from the ratio of the mass 30 peak to the mass 49 peak in the normal spectrum of BF₃. The actual magnitude for a given run is affected, along with other parameters, by the flow rate of fluorine and the position of the oxidant-inlet tube relative to the boron rod and the opening to the ion source of the mass spectrometer. Some of the variation in the BF⁺ intensity from one run to another can be attributed to the difficulty of reproducing the same conditions with regard to these two variables in our present equipment.

Although a rate expression for the reaction of boron with fluorine can not be calculated from the data obtained to date because of apparent variations in the fluorine flow and the BF₃ background, some generalizations can be made:




FIGURE I. SCHEMATIC DIAGRAM OF INLET SYSTEM FOR MASS SPECTROMETER




FIGURE 2. COMBUSTION APPARATUS FOR MASS SPECTROMETER

HEAT SHIELD REMOVED

TABLE I

INTENSITY (ARBITRARY UNITS) OF SPECTRAL PEAKS FOR BF,

m/e ^a	Ambient	800b	1060	1140	1250	1370	1470°K
11 (B+)	27.5	32.5	30.0	37.5	27.5	30.0	42.5
30 (BF ⁺)	20.0	25.0	25.0	29.5	20.0	25.0	30.0
48 (BF ₂ ⁺)	340	400	400	470	350	400	460
49 (BF ₂ ⁺)	1475	1750	1800	2000	1 500	1700	2000
68 (BF ₃ +)	97.5	110	110	125	95	105	125

Ratio of mass to charge.

TABLE II

RELATIVE INTENSITY OF SPECTRAL PEAKS FOR BF,

	Ambient	800a	1060	1140	1250	1370	1470°K	Av
B^+/BF_3^+	0.28	0.30	0.27	0.30	0.29	0.29	0.34b	0.30
BF ⁺ /BF ₃ ⁺	0.21	0.23	0.23	0.24	0.21	0.24	0.24	0.23
BF_2^+/BF_3^+	15.1	15.9	16.4	16.0	15.8	16.2	16.0	16.0

b Approximate.

a Approximate.

b Probably high because of vapor pressure of boron.

TABLE III

INTENSITY (ARBITRARY UNITS) OF SPECTRAL PEAKS FOR REACTION OF ¿LUORINE WITH A HEATED BORON ROD

m/e ^a	800b	1120	1220	1400	1600	1650°K
11 (B ⁺)	0.16	0.53	0.6	0.9	1.5	1.7
30 (BF ⁺)	2.8	4.6	5.7	7.0	10.5	10.0
49 (BF ₂ ⁺)	3.0	5.6	7.1	9.5	21.0	17.5
68 (BF ₃ ⁺)	0.30	0.44	0.60	0.62	1.4	1.3

aRatio of mass to charge.

TABLE IV

RELATIVE INTENSITY OF SPECTRAL PEAKS FOR REACTION OF FLUORINE WITH A HEATED BORON ROD

	Run		1120	1220		1400	1450	1500	1600	1650°K
BF ⁺ /BF ₃ ⁺	1	3.3			15.2		14.0		.4.0	2.5
	2	9.3	11.5	5.6		11.3			7.7	
	3		0.80	1.12	0.45			0.51		0.42
	4				0.70		0.42			0.36
	5		0.28	i	0.79		0.57			0.40
BF2 ⁺ /BF3 ⁺	1	15.			22.		22.		34.	46.
	2	10.	14.	12.		15.3			15.	
	3		15.8	11.3	12.7			17.3		16.4
	4				16.2			11.9		16.1
	5		16.7		16.1			10.2		12.6

^aApproximate.

bApproximate.

- (a) The ratio BF^+/BF_3^+ is considerably greater than that expected from electron impact with BF_3 (Table IV).
- (b) The ratio BF₂⁺/BF₃⁺ is approximately equal to that due to electron impact on BF₃ (Table IV).
- (c) The BF₃⁺ intensity increases with an increase in temperature and is apparently related to reactions on or desorption from surfaces other than the boron rod, such as the trap, radiation shield, and face plate.

(d) The BF⁺ intensity, generally, is only slightly dependent on temperature above 1200°K (Table V).

The last observation suggests the possibility of more than a single mechanism for the oxidation of boron with fluorine or of an activated desorption of BF from the boron surface.

MICROBALANCE EXPERIMENTS

The apparatus used to determine the rate of reaction of boron with fluorine is discussed in detail in reference 4b and is described only briefly here (see also Figure 3). The equipment consists of a high-purity polycrystalline boron rod suspended from a quartz helix inside a quartz reactor. Provision is made for admitting fluorine at low flow rates at pressures from 10^{-3} to 1 torr. The change in weight of the boron rod (approximately 3 mm in diameter and 26 mm long) is followed with a precision cathetometer. The rod is heated with an image furnace in which the filament of a 1000-w projection lamp operating at approximately 60 v is placed on the facal axis of one parabolic mirror and the boron rod on the axis of a similar mirror. The mirrors are formed by rolling a 4-by-6-inch metal sheet into the shape of a parabolic cylinder.

Experiments in which the boron rod at room temperature was exposed to fluorine gas at 1 to 200 μ Hg pressure for three to four hours gave no apparent change in the weight of the rod. However, with the boron rod approximately 600°K, a detectable weight change was observed. Figure 4 shows the experimental data for a typical run, and Table VI summarizes the results obtained at several pressures. The reaction rate appears to be more dependent on the flow rate of fluorine than on the pressure of fluorine. This would indicate that nearly all the fluorine reacted with the boron, a conclusion substantiated

TABLE V

BF⁺ INTENSITY (ARBITRARY UNITS) FOR REACTION OF FLUORINE WITH HEATED BORON ROD

Run	Ambient	800a	1120	1220	1300	1400	1450	1500	1600	1650°K
1		1.0			34.3		34.2		33.3	46.0
2		2.8	4.5	5.6		6.9			10.0	
3		0.7	2.7	3.4	3.8			3.9		3.4
4					16.6		16.4			10.9
5	0.2		0.7		7.8		10.8			9.7

TABLE VI

CONSUMPTION RATE OF BORON IN FLUORINE AT LOW PRESSURES (PRELIMINARY DATA)

Chamber Pressure,	Flow Rate, molecules/sec	Reaction Rate, molecules B/cm²-sec		
150.	1.7×10^{17}	2.8 x 10 ¹⁶		
100.	2.0	3.2		
73.	2.0	5. 1		
73.	1.3	2.7		
5.	0.9	2.4		
1.	0.6	1.6		
0.8	0.9	1.9		
0.8	0.6	1.0		

^aApproximate.




FIGURE 3. DIAGRAM OF COMBUSTION APPARATUS FOR KINETIC STUDIES




FIGURE 4. DECREASE IN LENGTH OF QUARTZ MICROBALANCE DURING REACTION OF BORON WITH FLUORINE GAS

by calculating a value of 5×10^{16} molecules/sec for the consumption of fluorine at 1μ (based on formation of BF₃) compared to a flow rate of 6×10^{16} molecules/sec. It is apparent from these preliminary experiments that the vacuum system will have to be modified to attain flow rates at which the reaction rate is independent of the flow.

FUTURE WORK

Experiments will be continued in the mass spectrometer and the microbalance apparatus. The mass-spectrometer experiments will be refined in an attempt to get reproducible ion intensities at various temperatures to determine the activation energy of the boron-fluorine surface reaction. An attempt will be made to modify the microbalance apparatus to conduct experiments at higher flow rates and permit the determination of the accommodation coefficient for the surface reaction.

REFERENCES

- (1) Claude P. Talley and Lloyd E. Line, Jr., "Combustion of Elemental Boron," Experiment Incorporated (a) TM-838, 1 June 1956; (b) TM-861, 1 September 1956; (c) TM-898, 1 December 1956.
- (2) Claude P. Talley, "Combustion of Elemental Boron," Experiment Incorporated (a) TM-920, 1 March 1957; (b) TM-952, 1 June 1957; (c) TM-1009, 1 November 1957; (d) TM-1012, 1 February 1958; (e) TM-1038, 1 May 1958; (f) TM-1065, 1 August 1958; (g) TM-1090, 1 November 1958; (h) TM-1094, 1 February 1959; (i) TM-1105, 1 May 1959; (j) TM-1157, 1 August 1959; (k) TM-1165, 1 November 1959; (l) TM-1182, 1 February 1960; (m) TM-1211, 1 May 1960.
- (3) Claude P. Talley, "Combustion of Elemental Boron," Texaco Experiment Incorporated TM-1269, 1 August 1960.
- (4) Claude P. Talley and Harry Woods, "Combustion of Elemental Boron,"
 Texaco Experiment Incorporated (a) TM-1270, 1 November 1960;
 (b) TM-1271, 1 February 1961; (c) TM-1272, 1 May 1961.
- (5) U. V. Henderson, Jr., and Harry P. Woods, "Combustion of Elemental Boron," Texaco Experiment Incorporated (a) TM-1274, 1 August 1961; (b) TM-1296, 1 November 1961.